

## THE GOLDEN FLOAT LIFT



# MANUAL CONTROLLER

- Weatherproof and waterproof polycarbonate housing
- Heavy duty, pedestal mounted controller provides years of trouble-free use
- No sensitive electronics or circuit boards
- Easily allows for manual adjustment
- No power needed when lowering the lift
- Raises and lowers lift up to 50% faster than competitors' controllers
- GFCI protection
- Power requirement: 120V, 15A



## **ELECTRONIC CONTROLLER**

- Weatherproof and waterproof polycarbonate housing
- User-friendly automated controller with manual override of the lift while lowering and raising
- Controller is pedestal mounted directly on the lift
- Built-in safety feature stops the lift in the event of power loss during operation
- GFCI protection
- Power requirement: 120V, 15A

**FOLLOW US** 













### THE GOLDEN FLOAT LIFT:

#### THE GOLDEN FLOAT LIFT IS A FREE-FLOATING, HYDROPNEUMATIC LIFT THAT IS PERFECT FOR SALT OR FRESH WATER

The Float Lift by Golden Boat Lifts is designed with a marine grade aluminum and stainless steel frame, 316 stainless steel hardware, and UV resistant polyethylene tanks. The Golden Floating Lift can be tied to a floating dock or installed with a conventional mooring system.

The Golden Float Lift comes standard with a trouble-free, maintenance-free, manual controller unit or with an optional, self-leveling electronic controller. This lift can be configured for nearly all boat types including standard V-hull, inboard wake, pontoon, tritoon and jet drive boats. The Floating Lift is compatible with fixed or floating docks, and works in a U-shaped slip, double-wide slip, L-shaped dock or square dock.

#### PERFECT FOR FRESH OR SALTWATER

Model	Capacity	Number of Tanks	Tank Capacity	Length	Outside Width	Water Depth (Minimum)
6000-422	6000 Lbs	4	1500 Lbs.	14'	Beam + 36"	25" + Draft of Boat w/ Engine Raised
8000-429	8000 Lbs	4	2000 Lbs.	14'	Beam + 36"	32" + Draft of Boat w/ Engine Raised
9000-622	9000 Lbs	6	1500 Lbs.	18' 6"	Beam + 36"	25" + Draft of Boat w/ Engine Raised
12000-629	12000 Lbs	6	2000 Lbs.	18' 6"	Beam + 36"	32" + Draft of Boat w/ Engine Raised
16000-829	16000 Lbs	8	2000 Lbs.	25'	Beam + 36"	32" + Draft of Boat w/ Engine Raised
20000-829	20000 Lbs	8 + 1 Auxiliary 48"x120"x24"	2000 Lbs.	25'	Beam + 36"	32" + Draft of Boat w/ Engine Raised
25000-829	25000	8+ 2 Auxiliary 48"x120"x24"	2000 Lbs.	25'	Beam + 36"	32" + Draft of Boat w/ Engine Raised
32000-1029	32000	10 + 3 Auxiliary 48"x120"x24"	2000 Lbs.	31'6"	Beam + 36"	32" + Draft of Boat w/ Engine Raised
35000-1029	35000	10 + 3 Auxiliary 48"x120"x32"	2000 Lbs.	31'6"	Beam + 36"	38" + Draft of Boat w/ Engine Raised



**UP TO 8,000 LBS** 



**UP TO 20,000 LBS** SINGLE AUX TANK



**UP TO 12,000 LBS** 



**UP TO 25,000 LBS DOUBLE AUX TANK** 



**UP TO 16,000 LBS** 



**UP TO 35,000 LBS TRIPLE AUX TANK** 





